

GBG 75E & GBG 95E

GENPOWER GENERATOR Gasoline Generator 230V - 50Hz & 110V - 60Hz



Features and Benefits

- Half century experience in generator manufacturing
- Gasoline engines with advanced technology and quality
- Alternators with advanced technology and quality
- Easy to Carry
- High quality and reliable technology
- Compact Design and Silent
- Suitable for heavy-duty
- Durable
- Wide range of affordable spare parts

- Low noise level
- Low exhaust emission
- Low operating cost
- Low fuel consumption
- Low oil consumption
- Lightweight
- Big Size Fuel Tank
- First class product support
- Global technical service and maintenance support

Generator General Information														
Generator Model	Frequency Hz	Voltage V	Power Factor CosQ	Speed rpm	Gasoline Engine		Alternator		Type of Operation	Generator Output				
					Brand	Model	Series	Brand	Model	Series	operation	kVA	kW	А
GBG 75E	50	230	0,8	3000	GENPOWER 190						Maximum	7,5	6,0	32,6
						E	GENPOWER	GNP	100L	Rated	6,3	5,0	27,4	
GBG 95E	60	110	0,0	3600							Maximum	9,3	7,4	84,5
GBG JJE		110		3000							Rated	7,4	5,9	67,3

Gasoline Engine General Data

- Single Cylinder, with Carburettor
- OHV (Over Head Valve) Technology
- 3000 rpm 50Hz / 3600 rpm 60Hz
- Air Cooled
- Electronic Ignition TCI System
- 4 StrokeBig Size and Silent Muffler
- Big Size Air Filter
- 12V Electric Start and Recoil Starting
- **Equipment and Features**
- Heavy Duty Type Strong Base Frame
- Robotic Painting with Heavy Duty Electrostatic Powder Paint
- Durable Vibration Chocks Between Generator-Chassis
- Big Size Fuel Tank
- Fuel Level Gauge
- Fuel Tank Cap, with Ventilation
- Grounding Terminal
- Low Oil Level Alarm and Protection

Gasoline Engine Technical Data

Brand		Genpower
Model		GBE 190F
Speed	rpm	3000 / 3600
Displacement	cm ³	420
Number of Cylinders		1
Bore x Stroke	mm	90 x 66

Dimensions

Width *	Net (with Box)- mm	520 (525)
Length *	Net (with Box)- mm	682 (687)

Important Note 1: Never use the generators in closed areas

Important Note 2: Wait 20 min for the generator to cool down before putting in fuel





GENPOWER RESERVES THE RIGHT TO CHANGE THE CATALOGUES, PRODUCTS, MODELS AND TECHNICAL SPECIFICATIONS

Alternator

- Synchron Alternator
- Single Phase 230V / 110V
- Self Excited
- Power Factor: Cos Q: 0,8 / 1,0
- H or F Insulation Class
- IP 23 Protection ClassFrequency: 50 Hz / 60 Hz
- %100 Copper Winding (Rotor and Stator)
- With AVR
- %10-15 Total Harmonic (THD)

Control Panel

- 2 pcs 16A Schuko witp Cap
- 1 pcs 12V DC Output
- 1 pcs Analoque Voltmeter
- 1 pcs Circuit Breaker
- 1 pcs Fuse
- 1 pcs Start Key
- 1 pcs Grounding Terminal

Cooling System		Air Cooled
Starting System	12V Elec	ctric Start and Recoil
Running Time- %50 loading	Hour	9
Fuel		Gasoline
Oil Capacity	lt	1,1
Fuel Tank Capacity	It	27
Height *	Net (with Box)- mm	555 (560)
Weight *	Net (with Box)- Kgr	86 (88)

* Without handle and wheel

Factory Address ASO II. Industrial Zone 2010 Street No: 18

ASO II. Industrial Zone 2010 Street No: 18 06909 Temelli-Sincan/Ankara, Turkey Tel/ Fax: +90(312) 641 32 22 - 641 32 23 genpower@genpower.com.tr www.genpower.com.tr