



Diesel Generator

230V - 50Hz & 110V - 60Hz

GDG 10000EC & GDG 11000EC



Features and Benefits

- Half Century Experience in Generator Manufacturing
- Gasoline Engines with Advanced Technology and Quality
- Alternators with Advanced Technology and Quality
- Easy to Carry
- High Quality and Reliable Technology
- Compact Design and Silent
- Suitable for Heavy-Duty
- Durable
- Wide Range of Affordable Spare Parts

- Low Noise Level
- Low Exhaust Emission
- Low Operating Cost
- Low Fuel Consumption
- Low Oil Consumption
- Light Weight
- Big Size Fuel Tank
- First Class Product Support
- Global Technical Service and Maintenance Support

Generator General Information														
Generator Model	Frequency Hz	Voltage	Power Factor	Speed rpm	Diesel Engine		Alternator		Type of Operation	Generator Output				
	112	,	CosQ	ipiii	Brand	Model	Series	Brand	Model	Series	Operation	kVA	kW	Α
GDG 10000EC	50	230	0.8	3000	GENPOWER	195	FE	GENPOWER	GNP 1	110L	Maximum	10,0	8,0	43,5
											Rated	8,5	6,8	37,0
GDG 11000EC	60	110	0,6	3600	GLIV OWEN 193						Maximum	11,0	8,8	100,0
	00	110		3000							Rated	9,5	7,6	86,4
We also make productions; 22	0, 230, 240, 110	/220, 115/2	30, 120/240, 22	20/380, 230/4	100, 240/415V and 50H	Iz or 60Hz								

Diesel Engine General Data

- Single Cylinder, with Injector and Fuel Pump
- Vertical Type
- 3000 rpm 50Hz / 3600 rpm 60Hz
- Air Cooled • Direct Injection
- 4 Stroke
- Big Size and Silent Muffler
- Big Size Air Filter
- 12V Electric Start

Equipment and Features

- Sound Proof Canopy (70-75 dBA)
- Robotic Painting with Electrostatic Powder Paint
- Heavy Duty Type Wheels and Handle
- Big Size Fuel Tank
- Fuel Level Gauge
- Fuel Tank Cap, with Ventilation
- Grounding Terminal

Dimensions

Width

Length

Low Oil Level Alarm and Protection

Diesel Engine Technical Data

Brand		Genpower
Model		GDE 195FE
Speed	rpm	3000 / 3600
Displacement	cm ³	532
Number of Cylinders		1
Bore x Stroke	mm	95 x 75

Net (with Box)- mm

Net (with Box)- mm

Alternator

- Synchron Alternator
- Single Phase 230V / 110V
- Self Excited
- Power Factor: Cos Q: 0,8 / 1,0
- H or F Insulation Class
- IP 23 Protection Class
- Frequency: 50 Hz / 60 Hz
- %100 Copper Winding (Rotor and Stator)
- With AVR
- %10-15 Total Harmonic (THD)

Control Panel

- 2 pcs 16A Schuko witp Cap
- 1 pcs 12V DC Output
- 1 pcs Digital Panel
- 1 pcs Circuit Breaker • 1 pcs ATS Socket
- 1 pcs Oil Lamp
- 1 pcs Grounding Terminal

Cooling System		Air Cooled
Starting System		12V Electric Start
Running Time- %50 loading	Hour	20
Fuel		Diese
Oil Capacity	It	1,65
Fuel Tank Capacity	It	30

Height	Net (with Box)- mm	850 (860)
Weight	Net (with Box)- Kgr	177 (180)

Important Note 1: Never use the generators in closed areas

Important Note 2: Wait 20 min for the generator to cool down before putting in fuel





550 (565)

935 (945)