GDG SERIES

GDG 10000TEC & GDG 11000TEC



Features and Benefits

- Half Century Experience in Generator Manufacturing
- Gasoline Engines with Advanced Technology and Quality
- Alternators with Advanced Technology and Quality
- Easy to Carry
- High Quality and Reliable Technology
- Compact Design and Silent
- Suitable for Heavy-Duty
- Durable
- Wide Range of Affordable Spare Parts

- Low Noise Level
- Low Exhaust Emission
- Low Operating Cost
- Low Fuel Consumption
- Low Oil Consumption
- Light Weight
- Big Size Fuel Tank
- First Class Product Support
- Global Technical Service and Maintenance Support

Generator General Information														
Generator Model	Frequency Hz	Voltage V	Power Factor	Speed rpm	Diesel Engine		Alternator			Type of Operation	Generator Output			
			CosQ	1pm	Brand	Model	Series	Brand	Model	Series	operadon	kVA	kW	Α
GDG 10000TEC	50	231/400	0.9	3000	GENPOWER	195 FE		fe genpower	GNP	110L	Maximum	10,0	8,0	14,5
							EE				Rated	8,5	6,8	12,3
GDG 11000TEC	60	277/480	0,8	3600							Maximum	11,0	8,8	13,3
	00	2111400		3000							Rated	9,5	7,6	11,4

We also make productions; 220, 230, 240, 110/220, 115/230, 120/240, 220/380, 230/400, 240/415V and 50Hz or 60Hz

Diesel Engine General Data

- Single Cylinder, with Injector and Fuel Pump
- Vertical Type
- 3000 rpm 50Hz / 3600 rpm 60Hz
- Air Cooled
- Direct Injection
- 4 Stroke
- Big Size and Silent Muffler
- Big Size Air Filter
- 12V Electric Start

Equipment and Features

- Sound Proof Canopy (70-75 dBA)
- Robotic Painting with Electrostatic Powder Paint
- Heavy Duty Type Wheels and Handle
- Big Size Fuel Tank
- Fuel Level Gauge
- Fuel Tank Cap, with Ventilation
- Grounding Terminal
- Low Oil Level Alarm and Protection

Diesel Engine Technical Data

Brand		Genpower
Model		GDE 195FE
Speed	rpm	3000 / 3600
Displacement	cm ³	532
Number of Cylinders		1
Bore x Stroke	mm	95 x 75

Dimensions

Width	Net (with Box)- mm	550 (565)	He
Length	Net (with Box)- mm	935 (945)	We

Important Note 1: Never use the generators in closed areas

Important Note 2: Wait 20 min for the generator to cool down before putting in fuel





Factory Address

- Alternator
- Synchron Alternator
- Three Phase 231/400V 277/480V
- Self Excited
- Power Factor: Cos Q: 0,8 / 1,0
- H or F Insulation Class • IP 23 Protection Class
- Frequency: 50 Hz / 60 Hz
- %100 Copper Winding (Rotor and Stator)
- With AVR
- %10-15 Total Harmonic (THD)

Control Panel

- 2 pcs 16A Schuko witp Cap
- 1 pcs 12V DC Output
- 1 pcs Digital Panel
- 1 pcs Circuit Breaker
- 1 pcs ATS Socket
- 1 pcs Oil Lamp
- 1 pcs Grounding Terminal

	Air Cooled
	12V Electric Start
Hour	20
	Diesel
lt	1,65
lt	30
	050 (000)
Net (with Box)- mm	850 (860)
Net (with Box)- Kgr	177 (180)
	It It Net (with Box)- mm



231/400V - 50Hz & 277/480V - 60Hz



