GDG SERIES

GDG 12000TEC & GDG 13000TEC



Features and Benefits

- Half Century Experience in Generator Manufacturing
- Gasoline Engines with Advanced Technology and Quality
- Alternators with Advanced Technology and Quality
- Easy to Carry
- High Quality and Reliable Technology
- Compact Design and Silent
- · Suitable for Heavy-Duty
- Durable
- Wide Range of Affordable Spare Parts

- Low Noise Level
- Low Exhaust Emission

GENPOWE

F N F R A

Diesel Generator

231/400V - 50Hz & 277/480V - 60Hz

- Low Operating Cost
- Low Fuel Consumption
- Low Oil Consumption
- Light Weight
- First Class Product Support

Generator General Information														
Frequency Voltage		Power Factor	Speed rpm	Diesel Engine		Alternator		Type of Operation	Generator Output					
	112	•	CosQ	1pm	Brand	Model	Series	Brand	Model	Series	operation	kVA	kW	Α
GDG 12000TEC 5	50	231/400	0,8	3000	GENPOWER	1100	F	Genpower	GNP	115L	Maximum	12,0	9,6	17,3
	50	231/400									Rated	10,0	8,0	14,5
GDG 13000TEC	60 277/480	077/400	0,0	3600							Maximum	13,0	10,4	15,7
GDG 13000TEC		211/480		3000							Rated	11,0	8,8	13,3

We also make productions; 220, 230, 240, 110/220, 115/230, 120/240, 220/380, 230/400, 240/415V and 50Hz or 60Hz

Diesel Engine General Data

- Single Cylinder, with Injector and Fuel Pump
- Vertical Type
- 3000 rpm 50Hz / 3600 rpm 60Hz
- Air Cooled
- Direct Injection
- 4 Stroke
- Big Size and Silent Muffler
- Big Size Air Filter
- 12V Electric Start

Equipment and Features

- Sound Proof Canopy (70-75 dBA) •
- Robotic Painting with Electrostatic Powder Paint
- Heavy Duty Type Wheels and Handle
- Big Size Fuel Tank
- Fuel Level Gauge
- Fuel Tank Cap, with Ventilation
- Grounding Terminal
- Low Oil Level Alarm and Protection

Diesel Engine Technical Data

Brand		Genpower
Model		GDE 1100FE
Speed	rpm	3000 / 3600
Displacement	cm ³	667
Number of Cylinders		1
Bore x Stroke	mm	100 x 85

Dimensions

Width	Net (with Box)- mm	680 (720)
Length	Net (with Box)- mm	1100 (1175)

Important Note 1: Never use the generators in closed areas

Important Note 2: Wait 20 min for the generator to cool down before putting in fuel





Self Excited

Synchron Alternator

Alternator

• Power Factor: Cos Q: 0,8 / 1,0

• Three Phase 231/400V - 277/480V

- H or F Insulation Class • IP 23 Protection Class
- Frequency: 50 Hz / 60 Hz
- %100 Copper Winding (Rotor and Stator)
- With AVR
- %10-15 Total Harmonic (THD)

Control Panel

- 1 pcs 16A CEE Schuko witp Cap and 1 pcs Terminal
- 1 pcs 12V DC Output
- 1 pcs Digital Panel
- 1 pcs Circuit Breaker
- 1 pcs ATS Socket 1 pcs Oil Lamp
- 1 pcs Grounding Terminal

Cooling System		Air Cooled
Starting System		12V Electric Start
Running Time- %50 loading	Hour	18
Fuel		Diesel
Oil Capacity	lt	2
Fuel Tank Capacity	lt	30
Height	Net (with Box)- mm	860 (875)
Weight	Net (with Box)- Kgr	210 (215)

O II. Industrial Zone 2010 Street No: 18 06909 Temelli-Sincan/Ankara, Turkey Tel/ Fax: +90(312) 641 32 22 - 641 32 23 genpower@genpower.com.tr www.genpower.com.tr

Big Size Fuel Tank

Global Technical Service and Maintenance Support

- English 01-2021@2021 GBG Series Generator