# **GDG** SERIES

# **GDG 7000ECX & GDG 8000ECX**



### Features and Benefits

- Half Century Experience in Generator Manufacturing
- · Gasoline Engines with Advanced Technology and Quality
- Alternators with Advanced Technology and Quality
- Easy to Carry
- High Quality and Reliable Technology
- Compact Design and Silent
- Suitable for Heavy-Duty
- Durable
- Wide Range of Affordable Spare Parts

- Low Noise Level
- Low Exhaust Emission

GENPOWE

**Diesel Generator** 

230V - 50Hz & 110V - 60Hz

- Low Operating Cost
- Low Fuel Consumption
- Low Oil Consumption
- Light Weight
- Big Size Fuel Tank
- First Class Product Support
- Global Technical Service and Maintenance Support

| ( | Genera | tor Ge | neral In | format | ion |
|---|--------|--------|----------|--------|-----|
|   |        |        |          |        |     |

| Generator Model  |      | Speed<br>rpm  | d Diesel Engine |       | Alternator   |         |            | Type of<br>Operation | Generator Output |         |           |     |      |      |
|--|------|---------------|-----------------|-------|--------------|---------|------------|----------------------|------------------|---------|-----------|-----|------|------|
|  | 112  | •             | CosQ            | 1 pin | Brand        | Model   | Series     | Brand                | Model            | Series  | operation | kVA | kW   | Α    |
| GDG 7000ECX  | ( 50 | <b>50</b> 230 | 0.8             | 3000  | GENPOWER 186 | 186 FAE | EAE        | Genpower             | GNP              |         | Maximum   | 7,0 | 5,6  | 30,4 |
| GDG / UUUEUX   |      |               |                 | 3000  |              |         |            |                      |                  |         | Rated     | 6,0 | 4,8  | 26,1 |
| GDG 8000ECX  | 60   | <b>D</b> 110  |                 | 3600  |              |         | ULIN- UWER |                      |                  | Maximum | 7,7       | 6,2 | 70,0 |      |
| GDG SUUCECX  |      |               |                 | 3000  |              |         |            |                      |                  |         | Rated     | 6,7 | 5,4  | 60,9 |
| No also make productions: 20, 20, 24, 140/20, 145/20, 120/24, 20/240, 20/240, 240/45V and 50Hz or 50Hz |      |               |                 |       |              |         |            |                      |                  |         |           |     |      |      |

ons; 220, 230, 240, 110/220, 115/230, 120/240, 220/380, 23

# **Diesel Engine General Data**

- Single Cylinder, with Injector and Fuel Pump
- Vertical Type
- 3000 rpm 50Hz / 3600 rpm 60Hz
- Air Cooled
- Direct Injection
- 4 Stroke
- Big Size and Silent Muffler
- Big Size Air Filter
- 12V Electric Start

#### **Equipment and Features**

- Super Silent Sound Proof Canopy (63-66 dBA) •
- Robotic painting with electrostatic powder paint
- Heavy Duty Type Wheels and Handle
- Big size fuel Tank
- Fuel level gauge
- Fuel Tank Cap, with ventilation
- Grounding Terminal
- Low oil level Alarm and Protection

#### **Diesel Engine Technical Data**

| Brand               |                 | Genpower    |
|---------------------|-----------------|-------------|
| Model               |                 | GDE 186FAE  |
| Speed               | rpm             | 3000 / 3600 |
| Displacement        | cm <sup>3</sup> | 418         |
| Number of Cylinders |                 | 1           |
| Bore x Stroke       | mm              | 86 x 72     |

# Dimensions

| Width  | Net (with Box)- mm | 645 (660)  | Height |
|--------|--------------------|------------|--------|
| Length | Net (with Box)- mm | 995 (1030) | Weight |

#### Important Note 1: Never use the generators in closed areas

Important Note 2: Wait 20 min for the generator to cool down before putting in fuel





## Alternator

- Synchron Alternator
- Single Phase 230V / 110V
- Self Excited
- Power Factor: Cos Q: 0,8 / 1,0
- H or F Insulation Class
- IP 23 Protection Class • Frequency: 50 Hz / 60 Hz
- %100 Copper Winding (Rotor and Stator)
- %10-15 Total Harmonic (THD)

#### **Control Panel**

- 1 pcs 16A, 1 pcs 32A CEE Schuko witp Cap
- 1 pcs 12V DC Output
- 1 pcs Multi Functions Digital Panel
- 1 pcs Circuit Breaker
- 1 pcs ATS Socket
- 1 pcs Oil Lamp
- 1 pcs Grounding Terminal

| Cooling System            |                     | Air Cooled         |
|---------------------------|---------------------|--------------------|
| Starting System           |                     | 12V Electric Start |
| Running Time- %50 loading | Hour                | 12                 |
| Fuel                      |                     | Diesel             |
| Oil Capacity              | lt                  | 1,65               |
| Fuel Tank Capacity        | lt                  | 14,5               |
|                           |                     |                    |
|                           |                     |                    |
| Height                    | Net (with Box)- mm  | 890 (910)          |
| neight                    | Net (With DOX)- min | 090 (910)          |
| Weight                    | Net (with Box)- Kgr | 207 (217)          |



• With AVR