

GLT SERIES

LIGHT TOWER

GENPOWER[®]
GENERATOR

GLT 7EC

STANDARD SPECIFICATIONS

GLT 7EC MODEL LIGHT TOWER

NUMBER AND POWER OF LAMPS	Optional 4x400W Metal Halide/ 4x200W LED / 4X300W LED	
LUMINOUS FLUX (lm)	Total 104000/ 200000lm	
LAMP MODEL	E40 /Led	
LAMP TYPE	Optional Metal Halide or LED	
LAMP PROTECTION GRADE	IP 65	
MAST	Optional 3-4-5 section	
MAST DRIVING TYPE	Mechanical	
LIFTING LIMIT (mm)	Optional 5-7 mt	
ROTATION ANGLE OF THE MAST	MANUEL	
ADJUSTABLE ANGLE	Standard is Fixed Type - 360° Optinal	
GENERATOR MODEL	GDG 7000 EC - WITH CANOPY	
GENERATOR TYPE	SINGLE PHASE WITH BRUSH ALTERNATOR	
ENGINE TYPE	SINGLE CYLINDER, VERTICAL, 4 STROKE, AIR COOLED DIESEL	
ENGINE SPEED (RPM)	3000	3600
ENGINE STARTING SYSTEM	ELECTRIC/ KEY START	
VOLTAGE	230 V	120 V/ 240 V
RATED FREQUENCY (Hz)	50 Hz	60 Hz
INSULATION CLASS	F	
RATED POWER (KVA)	6	6,6
MAX POWER (KVA)	7	7,7
OUTPUT SOCKET	SINGLE PHASE SOCKET	
FUEL TANK CAPACITY (L)	30	
FUEL TANK TYPE	UPPER TANK	
CONTINUOUS RUNING TIME (hrs)	20	
ENGINE OIL	SAE 15W40/ SAE 10W30	
DRY WEIGHT (Kg)	380	
DIMENSIONS (LxMxH) (mm)	1600x1100x1550	
WHEEL MODEL	185R14C	
WHEEL TYPE	RUBBER TYRE	
SUPPORT LEG TYPE	HAND OPERATED	

FEATURES AND BENEFITS

- **EASY TRANSPORT**
- **EFFECTIVE USING**
- **HEAVY DUTY DESIGN**
- **DURABILITY**
- **COMPACT**
- **LOW NOISE LEVEL**
- **LOW OPERATING COST**
- **GLOBAL TECHNICAL SERVICE AND MAINTENANCE SUPPORT**



TECHNICAL SPECIFICATIONS



Factory Address
ASO II. Industrial Zone, 2010 Street No: 18, 06809 Temelli-Sincan/Ankara, Turkey
Tel/ Fax: +90(312) 641 32 22 - 641 32 32
info@genpower.com.tr & genpower@genpower.com.tr
www.genpower.com.tr



ISO 9001:2008
OHSAS 18001:2007
ISO 14001:2004

